



Univar USA Inc Safety Data Sheet

---

SDS No:

Version No:

Order No:

3075 Highland Pkwy, Ste 200, Downers Grove, IL 60515  
(425) 889 3400

---

Emergency Assistance

For emergency assistance involving chemicals call  
Chemtrec - (800) 424-9300



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** CAIROX® potassium permanganate

**Other means of identification**  
**SDS number** -

**Recommended use** Potassium Permanganate is an oxidant recommended for applications that require a strong oxidant.

**Recommended restrictions** Use in accordance with supplier's recommendations.

**Manufacturer / Importer / Supplier / Distributor information**

**Manufacturer/Supplier** CARUS CORPORATION  
**Address** 315 Fifth Street,  
Peru, IL 61354, USA  
**Telephone** 815 223-1500 - All other non-emergency inquiries about the product should be directed to the company  
**E-mail** salesmkt@caruscorporation.com  
**Website** www.caruscorporation.com  
**Contact person** Dr. Chithambarathanu Pillai  
**Emergency Telephone** For Hazardous Materials [or Dangerous Goods] Incidents ONLY (spill, leak, fire, exposure or accident), call CHEMTREC at CHEMTREC®, USA: 001 (800) 424-9300  
CHEMTREC®, Mexico (Toll-Free - must be dialed from within country): 01-800-681-9531  
CHEMTREC®, Other countries: 001 (703) 527-3887

## 2. Hazard(s) identification

<b>Physical hazards</b>	Oxidizing solids	Category 2
<b>Health hazards</b>	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 1B
	Serious eye damage/eye irritation	Category 1
	Specific target organ toxicity, single exposure	Category 1 (Respiratory System)
	Specific target organ toxicity, repeated exposure	Category 1 (Respiratory System, Central Nervous System)
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



**Signal word** Danger

**Hazard statement** May intensify fire; oxidizer. Harmful if swallowed. Causes severe skin burns and eye damage. Causes damage to organs (Respiratory System). Causes damage to organs (Respiratory System, Central Nervous System) through prolonged or repeated exposure.

### Precautionary statement

**Prevention** Keep away from heat. Keep/Store away from clothing and other combustible materials. Take any precaution to avoid mixing with combustibles. Do not breathe dust. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product.

**Response** In case of fire: Use water for extinction. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If exposed: Call a poison center/doctor.

**Storage** Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Not classified.

**Environmental hazards**  
 Hazardous to the aquatic environment, acute hazard Category 1  
 Hazardous to the aquatic environment, long-term hazard Category 1

**Supplemental information**

**Hazard symbol**



**Hazard statement** Very toxic to aquatic life with long lasting effects.

**Precautionary statement**

**Prevention** Avoid release to the environment.  
**Response** Collect spillage.

**3. Composition/information on ingredients**

**Substances**

Chemical name	Common name and synonyms	CAS number	%
Potassium permanganate		7722-64-7	> 97.5

**Composition comments** All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**4. First-aid measures**

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. Get medical attention immediately.

**Skin contact** Take off immediately all contaminated clothing. Immediately flush skin with plenty of water. Get medical attention immediately. Wash contaminated clothing before reuse.

Contact with skin may leave a brown stain of insoluble manganese dioxide. This can be easily removed by washing with a mixture of equal volume of household vinegar and 3% hydrogen peroxide, followed by washing with soap and water.

**Eye contact** Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids wide apart. Continue rinsing. Get medical attention immediately.

**Ingestion** Immediately rinse mouth and drink plenty of water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately.

**Most important symptoms/effects, acute and delayed** Contact with this material will cause burns to the skin, eyes and mucous membranes. Permanent eye damage including blindness could result.

**Indication of immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Decomposition products are alkaline. Brown stain is insoluble manganese dioxide.

**General information** In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. For personal protection, see Section 8 of the SDS. Wash contaminated clothing before reuse.

**5. Fire-fighting measures**

**Suitable extinguishing media** Flood with water from a distance, water spray or fog.

**Unsuitable extinguishing media** The following extinguishing media are ineffective: Dry chemical. Foam. Carbon dioxide (CO2). Halogenated materials.

**Specific hazards arising from the chemical** May intensify fire; oxidizer. May ignite combustibles (wood, paper, oil, clothing, etc.). Contact with incompatible materials or heat (135 °C / 275 °F) could result in violent exothermic chemical reaction. Oxidizing agent, may cause spontaneous ignition of combustible materials. By heating and fire, corrosive vapors/gases may be formed.

**Special protective equipment and precautions for firefighters** Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Dike fire control water for later disposal. Water runoff can cause environmental damage.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up**

Keep combustibles (wood, paper, oil, etc.) away from spilled material. Should not be released into the environment. This product is miscible in water. Stop leak if possible without any risk. Dike the spilled material, where this is possible. Clean up spills immediately by sweeping or shoveling up the material. Do not return spilled material to the original container; transfer to a clean metal or plastic drum. To clean up potassium permanganate solutions, follow either of the following two options:

Option # 1: Dilute to approximately 6% with water, and then reduce with sodium thiosulfate, a bisulfite or ferrous salt solution. The bisulfite or ferrous salt may require some dilute sulfuric acid (10% w/w) to promote reduction. Neutralize with sodium carbonate to neutral pH, if acid was used. Decant or filter and deposit sludge in approved landfill. Where permitted, the sludge may be drained into sewer with large quantities of water.

Option # 2: Absorb with inert media like diatomaceous earth or inert floor dry, collect into a drum and dispose of properly. Do not use saw dust or other incompatible media. Disposal of all materials shall be in full and strict compliance with all federal, state, and local regulations pertaining to permanganates.

To clean contaminated floors, flush with abundant quantities of water into sewer, if permitted by federal, state, and local regulations. If not, collect water and treat as described above.

Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS.

**Environmental precautions**

Do not allow to enter drains, sewers or watercourses. Contact local authorities in case of spillage to drain/aquatic environment.

**7. Handling and storage**

**Precautions for safe handling**

Take any precaution to avoid mixing with combustibles. Do not get this material in your eyes, on your skin, or on your clothing. Do not breathe dust or mist or vapor of the solution. Use personal protection as recommended in Section 8 of the SDS. If clothing becomes contaminated, remove and wash off immediately. When using, do not eat, drink or smoke. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Avoid release to the environment.

**Conditions for safe storage, including any incompatibilities**

Store locked up. Keep container tightly closed and in a well-ventilated place. Store in a cool, dry place. Store away from incompatible materials (See Section 10). Store in accordance with NFPA 430 requirements for Class II oxidizers.

**8. Exposure controls/personal protection**

**Occupational exposure limits**

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Potassium permanganate (CAS 7722-64-7)	Ceiling	5 mg/m3

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Potassium permanganate (CAS 7722-64-7)	TWA	0.1 mg/m3	Inhalable fraction.
		0.02 mg/m3	Respirable fraction.

**US NIOSH Pocket Guide to Chemical Hazards: Recommended exposure limit (REL)**

Components	Type	Value	Form
Potassium permanganate (CAS 7722-64-7)	TWA	1 mg/m3	Fume.

**US NIOSH Pocket Guide to Chemical Hazards: Short Term Exposure Limit (STEL)**

Components	Type	Value	Form
Potassium permanganate (CAS 7722-64-7)	STEL	3 mg/m3	Fume.

No biological exposure limits noted for the ingredient(s).  
Follow standard monitoring procedures.  
Provide adequate general and local exhaust ventilation. An eye wash and safety shower must be available in the immediate work area.

**Appropriate engineering controls**

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles). Wear face shield if there is risk of splashes.

**Skin protection**

**Hand protection** Wear chemical-resistant, impervious gloves. Use protective gloves made of: Rubber or plastic. Suitable gloves can be recommended by the glove supplier.

**Other** Wear appropriate chemical resistant clothing. Rubber or plastic apron.

**Respiratory protection** In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment with particle filter. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.

Measurement Element: Manganese (Mn)

10 mg/m3

Any particulate respirator equipped with an N95, R95, or P95 filter (including N95, R95, and P95 filtering facepieces) except quarter-mask respirators. The following filters may also be used: N99, R99, P99, N100, R100 or P100.

Any supplied-air respirator.

25 mg/m3

Any supplied-air respirator operated in a continuous-flow mode.

Any powered, air-purifying respirator with a high-efficiency particulate filter.

50 mg/m3

Any air-purifying, full-face piece respirator equipped with an N100, R100, or P100 filter.

Any supplied-air respirator with a tight-fitting face piece that is operated in a continuous-flow mode.

Any powered, air-purifying respirator with a tight-fitting face piece and a high-efficiency particulate filter.

Any self-contained breathing apparatus with a full face piece.

Any supplied-air respirator with a full face piece.

500 mg/m3

Any supplied-air respirator operated in a pressure-demand or other positive-pressure mode.

Emergency or planned entry into unknown concentrations or IDLH conditions -

Any self-contained breathing apparatus that has a full face piece and is operated in a pressure-demand or other positive-pressure mode.

Escape

Any air-purifying, full-face piece respirator equipped with an N100, R100, or P100 filter.

Any appropriate escape-type, self-contained breathing apparatus.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Keep from contact with clothing and other combustible materials. Remove and wash contaminated clothing promptly. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

**9. Physical and chemical properties**

**Appearance** Dark purple solid with metallic luster.

**Physical state** Solid.

**Form** Solid.

**Color** Dark purple.

**Odor** Odorless.

**Odor threshold** Not available.

**pH** Not applicable.

**Melting point/freezing point** Starts to decompose with evolution of oxygen (O2) at temperatures above 150 °C. Once initiated, the decomposition is exothermic and self sustaining.

**Initial boiling point and boiling range** Not applicable.

**Flash point** Not applicable.

**Evaporation rate** Not applicable.

**Flammability (solid, gas)** Non flammable.

**Upper/lower flammability or explosive limits**

<b>Flammability limit - lower (%)</b>	Not applicable.
<b>Flammability limit - upper (%)</b>	Not applicable.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.

<b>Vapor pressure</b>	Not applicable.
<b>Vapor density</b>	Not applicable.
<b>Relative density</b>	2.7 (20 °C) ( Water = 1)
<b>Solubility(ies)</b>	6 % (20 °C) 20 % (65 °C)
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not applicable.

**Other information**

<b>Explosive properties</b>	Not explosive. Can explode in contact with sulfuric acid, peroxides and metal powders.
<b>Molecular weight</b>	158.03
<b>Oxidizing properties</b>	Strong oxidizing agent.

**10. Stability and reactivity**

<b>Reactivity</b>	The product is non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Stable at normal conditions.
<b>Possibility of hazardous reactions</b>	Contact with combustible material may cause fire. Can explode in contact with sulfuric acid, peroxides and metal powders. Starts to decompose with evolution of oxygen (O2) at temperatures above 150 °C. Once initiated, the decomposition is exothermic and self sustaining.
<b>Conditions to avoid</b>	Contact with incompatible materials or heat (135 °C / 275 °F) could result in violent exothermic chemical reaction.
<b>Incompatible materials</b>	Acids. Peroxides. Reducing agents. Combustible material. Metal powders. Contact with hydrochloric acid liberates chlorine gas.
<b>Hazardous decomposition products</b>	By heating and fire, corrosive vapors/gases may be formed.

**11. Toxicological information**

**Information on likely routes of exposure**

<b>Ingestion</b>	Harmful if swallowed.
<b>Inhalation</b>	May cause irritation to the respiratory system.
<b>Skin contact</b>	Causes severe skin burns.
<b>Eye contact</b>	Causes serious eye damage.

**Symptoms related to the physical, chemical and toxicological characteristics**  
 Contact with this material will cause burns to the skin, eyes and mucous membranes. Permanent eye damage including blindness could result.

**Information on toxicological effects**

**Acute toxicity** Harmful if swallowed.

Components	Species	Test Results
Potassium permanganate (CAS 7722-64-7)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rat	2000 mg/kg
<i>Oral</i>		
LD50	Rat	2000 mg/kg

<b>Skin corrosion/irritation</b>	Causes severe skin burns.
<b>Serious eye damage/eye irritation</b>	Causes serious eye damage.

Respiratory sensitization	Not classified.
Skin sensitization	Not classified.
Germ cell mutagenicity	Not classified.
Carcinogenicity	Not classified.
Reproductive toxicity	Not classified.
Specific target organ toxicity - single exposure	Causes damage to organs (respiratory system).
Specific target organ toxicity - repeated exposure	Causes damage to organs (respiratory system, central nervous system) through prolonged or repeated exposure.
Aspiration hazard	Not classified.
Chronic effects	May cause damage to respiratory system. Prolonged exposure, usually over many years, to manganese oxide fume/dust can lead to chronic manganese poisoning, chiefly affecting the central nervous system.

## 12. Ecological information

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Components	Species	Test Results	
Potassium permanganate (CAS 7722-64-7)			
<b>Aquatic</b>			
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	2.7 mg/l, 96 hours, static
			2.3 mg/l, 96 hours, flow through
			2.3 mg/l, 96 hours
			1.8 - 5.6 mg/l
	Carp ( <i>Cyprinus carpio</i> )	3.16 - 3.77 mg/l, 96 hours	
		2.97 - 3.11 mg/l, 96 hours	
		3.3 - 3.93 mg/l, 96 hours, static	
	Goldfish ( <i>Carassius auratus</i> )	Milkfish, salmon-herring ( <i>Chanos chanos</i> )	> 1.4 mg/l, 96 hours
			Rainbow trout ( <i>Oncorhynchus mykiss</i> )
	Rainbow trout, donaldson trout ( <i>Oncorhynchus mykiss</i> )	Rainbow trout, donaldson trout ( <i>Oncorhynchus mykiss</i> )	1.8 mg/l, 96 hours
1.08 - 1.38 mg/l, 96 hours			
0.77 - 1.27 mg/l, 96 hours			
		0.275 - 0.339 mg/l, 96 hours	

<b>Persistence and degradability</b>	Expected to be readily converted by oxidizable materials to insoluble manganese oxide.
<b>Bioaccumulative potential</b>	Potential to bioaccumulate is low.
<b>Mobility in soil</b>	The product is miscible with water. May spread in water systems.
<b>Other adverse effects</b>	None known.

## 13. Disposal considerations

<b>Disposal instructions</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazardous waste code</b>	D001: Ignitable waste The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Do not allow this material to drain into sewers/water supplies.
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Rinse container at least three times to an absence of pink color before disposing. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

<b>DOT</b>	
<b>UN number</b>	UN1490
<b>UN proper shipping name</b>	Potassium permanganate
<b>Transport hazard class(es)</b>	5.1
<b>Subsidiary class(es)</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	Yes

Annotation:

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Special provisions** iB8, iP2, iP4, T3, TP33  
**Packaging exceptions** 152  
**Packaging non bulk** 212  
**Packaging bulk** 240

**IATA**

**UN number** UN1490  
**UN proper shipping name** Potassium permanganate  
**Transport hazard class(es)** 5.1  
**Subsidiary class(es)** -  
**Packaging group** II  
**Environmental hazards** Yes  
**Labels required** 5.1  
**ERG Code** 5L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IMDG**

**UN number** UN1490  
**UN proper shipping name** POTASSIUM PERMANGANATE  
**Transport hazard class(es)** 5.1  
**Subsidiary class(es)** -  
**Packaging group** II  
**Environmental hazards**  
**Marine pollutant** Yes  
**Labels required** 5.1  
**EmS** F-H, S-Q  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**15. Regulatory information**

**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.  
  
CERCLA/SARA Hazardous Substances - Not applicable.  
  
Drug Enforcement Administration (DEA) (21 CFR 1310.02 (b) 8): List II chemical.  
  
Department of Homeland Security (DHS) Chemical Facility Anti-Terrorism Standards (6 CFR 27, Appendix A): Listed.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Potassium permanganate	7722-64-7	> 97.5

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Potassium permanganate (CAS 7722-64-7)



## Annotation

Not regulated.

**Clean Water Act (CWA)  
Section 112(r) (40 CFR  
68.130)** Hazardous substance**Safe Drinking Water Act  
(SDWA)** Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and  
Chemical Code Number**

Potassium permanganate (CAS 7722-64-7) 6579

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Potassium permanganate (CAS 7722-64-7) 15 % wt

**DEA Exempt Chemical Mixtures Code Number**

Potassium permanganate (CAS 7722-64-7) 6579

**Food and Drug  
Administration (FDA)** Not regulated.**US state regulations** This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

California OSH Hazardous Substance List: Listed.

**US. Massachusetts RTK - Substance List**

Potassium permanganate (CAS 7722-64-7)

**US. New Jersey Worker and Community Right-to-Know Act**

Potassium permanganate (CAS 7722-64-7) 500 lbs

**US. Pennsylvania RTK - Hazardous Substances**

Potassium permanganate (CAS 7722-64-7)

**US. Rhode Island RTK**

Not regulated.

**US. California Proposition 65****US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Not listed.

**International Inventories**


Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

**Issue date** 27-November-2013  
**Revision date** -  
**Version #** 01



**List of abbreviations**

GHS: Globally Harmonized System of Classification and Labeling of hazardous properties of Chemicals.  
TWA: Time weighted average.  
LD50: Lethal Dose, 50%.  
LC50: Lethal Concentration, 50%.  
IMDG: International Maritime Dangerous Goods.  
IATA: International Air Transport Association.  
MARPOL: International Convention for the Prevention of Pollution from Ships.

**References**

HSDB® - Hazardous Substances Data Bank  
Registry of Toxic Effects of Chemical Substances (RTECS)  
IARC Monographs. Overall Evaluation of Carcinogenicity  
National Toxicology Program (NTP) Report on Carcinogens  
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

**Disclaimer**

The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change and, therefore, holders and users should satisfy themselves that they are aware of all current data and regulations relevant to their particular use of product. CARUS CORPORATION DISCLAIMS ALL LIABILITY FOR RELIANCE ON THE COMPLETENESS OR ACCURACY OR THE INFORMATION INCLUDED HEREIN. CARUS CORPORATION MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE OR PURPOSE OF THE PRODUCT DESCRIBED HEREIN. All conditions relating to storage, handling, and use of the product are beyond the control of Carus Corporation, and shall be the sole responsibility of the holder or user of the product.

(Carus and design) is a registered service mark of Carus Corporation. CAIROX® is a registered trademark of Carus Corporation. Copyright 1998.

**This SDS contains revisions in the following section(s):**

This safety data sheet contains revisions in the following section(s):

## Univar USA Inc Safety Data Sheet

---

For Additional Information contact SDS Coordinator during business hours, Pacific time: (425) 889-3400

### **Notice**

Univar USA Inc. ("Univar") expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this SDS as a product specification. For product specification information refer to a product specification sheet and/or a certificate of analysis. These can be obtained from your local Univar sales office.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Univar makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Univar's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process